Distributed by:

JAMECO® ELECTRONICS

**www.Jameco.com ✦ 1-800-831-4242**

The content and copyrights of the attached material are the property of its owner.

# Double Row Terminal Blocks

## Kulka® 601 GP Series

### 300 Volts

**Jameco Part Number 188672**

**Specifications:**

Base, General Purpose Phenolic, 150° C
JJ (GDI-30F) material is available
Open Back Design
Screws, #6-32 Binder Head, Phil-Slot
Terminals, Plated Brass
1-23 Poles
7/16" Centers
Wire Range with Wire Binding Screw #12 - #22 Awg - 20 Amps
Will Accommodate Lugs for Wire Sizes #10 - #16 Awg - 30 Amps
The Suitability of These Devices for Greater Currents Shall Be Determined in the End-Use Application.
UL Recognized File No. E47811
CSA Certified File No. LR19766
CE

| Catalog # | # of poles | Dimensions | |
|---|---|---|---|
| | | A | B |
| 601 GP 01 | 1 | 1.19 | 0.88 |
| 601 GP 02 | 2 | 1.62 | 1.31 |
| 601 GP 03 | 3 | 2.06 | 1.75 |
| 601 GP 04 | 4 | 2.50 | 2.19 |
| 601 GP 05 | 5 | 2.94 | 2.63 |
| 601 GP 06 | 6 | 3.37 | 3.06 |
| 601 GP 07 | 7 | 3.81 | 3.50 |
| 601 GP 08 | 8 | 4.25 | 3.94 |
| 601 GP 09 | 9 | 4.69 | 4.38 |
| 601 GP 10 | 10 | 5.12 | 4.81 |
| 601 GP 11 | 11 | 5.56 | 5.25 |
| 601 GP 12 | 12 | 6.00 | 5.69 |

Top Mounted Hardware is .250" Wide

| Catalog # | # of poles | Dimensions | |
|---|---|---|---|
| | | A | B |
| 601 GP 13 | 13 | 6.44 | 6.13 |
| 601 GP 14 | 14 | 6.87 | 6.56 |
| 601 GP 15 | 15 | 7.31 | 7.00 |
| 601 GP 16 | 16 | 7.75 | 7.44 |
| 601 GP 17 | 17 | 8.19 | 7.88 |
| 601 GP 18 | 18 | 8.62 | 8.31 |
| 601 GP 19 | 19 | 9.06 | 8.75 |
| 601 GP 20 | 20 | 9.50 | 9.19 |
| 601 GP 21 | 21 | 9.94 | 9.63 |
| 601 GP 22 | 22 | 10.37 | 10.06 |
| 601 GP 23 | 23 | 10.81 | 10.50 |

MM=Dim X 25.4

**Hardware Options:**

| | | | |
|---|---|---|---|
| KT 37 | = | Full Quick Connect (0° flat) | See Page 87 |
| KT 38 | = | Full Quick Connect (45° Bend) | See Page 87 |
| KT 39 | = | Full Quick Connect (90° Bend) | See Page 87 |
| ST | = | Full Solder | See Page 88 |
| LL(J601) | = | Line to Line Jumper | See Page 90 |
| 3/4 ST | = | Half Solder | See Page 88 |
| KT 43 | = | Half Quick Connect (0° Flat) | See Page 87 |
| KT 44 | = | Half Quick Connect (45° Bend) | See Page 87 |
| KT 45 | = | Half Quick Connect (90° Bend) | See Page 87 |
| 3765 | = | Wire Clamp Screw | See Page 90 |
| Y | = | Feed Thru Solder (.422) | See Page 89 |
| YSY | = | Feed Thru Solder (.687) | See Page 89 |
| 2102 | = | Stud | See Page 92 |
| 2104 | = | Feed Thru Solder | See Page 92 |
| 2108 | = | Individual Screw Terminals | See Page 92 |